## 32" PVM



- ◆ 32" 1920×1080 LCD display screen
- ◆ Built-in 2 Mega Pixel AI Camera
- Protective Glass / Wider Viewing Angle 178° / 178°
- Support Chrome, Firefox and Edge to set
- Onvif Profile S
- Support image advertising
- Display mode: Full screen video, full screen advertising
- ◆ Pop-up deterence sign when detected person by Face/motion/PIR
- ◆ Up load LOGO by end user
- ◆ Powered by Linux OS. More stable and cost effective

	Display
Screen Size	32 "
Resolution	1920×1080 Pixel
Brightness	300cd/m²
Contrast Ratio	1000 : 1
Viewing Angle(H/V)	178°/ 178°
Display Colors	16.7 Million
Response Time	< 30 ms
	Camera
Sensor	1/2.9", 2MP CMOS
Resolution	1920×1080

EMMC/Flash	512MB
DDR/RAM	1GB
Lens	3.3mm (H:80±4°,V:47±3°)
Video Compression	H.264 / H.265
Motion Detection	Support
Ethernet Port	RJ45×1 10M/100M
Communication	RJ45/WIFI
Web Application	Support Chrome, Firefox and Edge
Integration Protocol	ONVIF Profile S, API
Image Setting	Contrast, Brightness, Sharpness, Saturation, BLC, WDR, HLC, 3DNR
Trigger Events	PIR/Motion Detection/Face Detection/ Alarm in
Storage	TF Card / NVR
Brand Custo	
Pop-up Deterrence Message	png
Voice Prompt	wav
Brand Logo	png
Picture Format	
ricture rominat	jpg、png、bmp、gif(resolution:1920*1080)
	Full screen video: 1920×1080
Display Mode	Full screen video: 1920×1080 Full screen advertising: 1920×1080
	Full screen video: 1920×1080
Display Mode	Full screen video: 1920×1080 Full screen advertising: 1920×1080
Display Mode	Full screen video: 1920×1080 Full screen advertising: 1920×1080 Pending
Display Mode  Total Ads File Size	Full screen video: 1920×1080 Full screen advertising: 1920×1080 Pending Interface
Display Mode  Total Ads File Size  Alarm Interface	Full screen video: 1920×1080 Full screen advertising: 1920×1080 Pending Interface Input/Output×1
Display Mode  Total Ads File Size  Alarm Interface Audio	Full screen video: 1920×1080 Full screen advertising: 1920×1080 Pending Interface Input/Output×1 Built in Speaker×2 5W
Display Mode  Total Ads File Size  Alarm Interface Audio USB	Full screen video: 1920×1080 Full screen advertising: 1920×1080 Pending Interface Input/Output×1 Built in Speaker×2 5W Micro USB×1
Display Mode  Total Ads File Size  Alarm Interface Audio  USB  TF Card	Full screen video: 1920×1080 Full screen advertising: 1920×1080 Pending Interface Input/Output×1 Built in Speaker×2 5W Micro USB×1 TF Card Slot×1 (Max Support:1TB)
Display Mode  Total Ads File Size  Alarm Interface Audio  USB  TF Card  PIR Sensor	Full screen video: 1920×1080 Full screen advertising: 1920×1080 Pending Interface Input/Output×1 Built in Speaker×2 5W Micro USB×1 TF Card Slot×1 (Max Support:1TB) ×1
Display Mode  Total Ads File Size  Alarm Interface Audio  USB  TF Card  PIR Sensor  Ethernet 10 / 100	Full screen video: 1920×1080 Full screen advertising: 1920×1080 Pending  Inter/acc  Input/Output×1 Built in Speaker×2 5W Micro USB×1 TF Card Slot×1 (Max Support:1TB) ×1 RJ45×1 ×1(Once triggered in emergency circumstances, the device will
Display Mode  Total Ads File Size  Alarm Interface Audio  USB  TF Card  PIR Sensor  Ethernet 10 / 100	Full screen video: 1920×1080 Full screen advertising: 1920×1080  Pending  Inter/ace  Input/Output×1  Built in Speaker×2 5W  Micro USB×1  TF Card Slot×1 (Max Support:1TB)  ×1  RJ45×1  ×1(Once triggered in emergency circumstances, the device will play a preset picture to alert.)

## Dimension

